

Plantcohydro WaterTank



Technical information

Available capacities

Available capacities	Size (length x width)	Height theoretical in m	Unloaded weight	Tarpaulin weight*	Total weight
1 000 liters	2 m x 1 m	0,50 m	7,5 kg	0,8 kg	8,3 kg
6 000 liters	4 m x 3 m	0,50 m	18 kg	2 kg	20 kg
12 000 liters	5 m x 4 m	0,60 m	31 kg	3 kg	34 kg
25 000 liters	7,5 m x 4 m	0,83 m	43 kg	4,5 kg	47,5 kg
50 000 liters	15 m x 4 m	0,83 m	82 kg	8 kg	90 kg
100 000 liters	30 m x 4 m	0,83 m	162 kg	16 kg	178 kg

*included with the tank



Technical information

Tank

Composition	PE and PP Multilayers
Temperature resistance	-20°C to 70°C
Color	Black

Valves

Composition	PP and fiberglass composite; fluorine rubber seals
Size	DN 80
Recommended connection	Camlock DN 80**
Maximum nominal flow	800L/min
Maximum pressure	4 Bars
Maximum operating temperature	70°C



** Example of camlock

CCTP description:

Multi-layer flexible tanks (PP and PE), equipped with 3 DN80 butterfly valves. Capacity 1000 L; 6000 L; 12000 L; 25000 L; 50000 L and 100000 L. Type Plantco WaterTank or equivalent.

